NSN 5305-00-951-5443

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-951-5443 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.231 inches and 0.312 inches **Fastener Length:** Between 0.281 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.178 inches and 0.183 inches **Head Height:** Between 0.059 inches and 0.069 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Hardness Rating:** Between 248.0 brinell standard and 321.0 brinell standard **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5735 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0

NSN 5305-00-951-5443

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.