NSN 5305-00-952-7403

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-952-7403 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.210 inches and 0.230 inches **Fastener Length:** Between 0.395 inches and 0.405 inches **Head Style:** Round w/wrench flats chamfered **Head Diameter:** Between 0.280 inches and 0.290 inches **Head Height:** Between 0.045 inches and 0.055 inches Width Between Flats: Between 0.240 inches and 0.250 inches **Shoulder Diameter:** 0.2087 inches first shoulder and 0.2092 inches first shoulder **Shoulder Length:** 0.145 inches first shoulder and 0.155 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 40 Hardness Rating: 37.0 rockwell c and 44.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Stainless steel **Special Test Features:**

Concentric hole in shank, 0.078 in. Dia, 0.090 in. Depth **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-00-952-7403

Shoulder Screw - Page 2 of 2



Fiig:

A003b0