NSN 5305-00-953-7032

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-953-7032 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.366 inches **Fastener Length:** 2.562 inches **Head Style:** Flat chamfer **Head Diameter:** 0.218 inches **Head Height:** 0.500 inches First Diameter From Head: 0.120 inches **Second Diameter From Head:** 0.218 inches **Third Diameter From Head:** 0.120 inches **Fourth Diameter From Head:** 0.250 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.070 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.120 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 2.000 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 2.040 inches **Internal Drive Style: Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:**

4

Material:

Steel comp 303 or steel comp 304

Material Specification:

Astm a582, cond a assn standard 1st material response or astm a581, cond a assn standard 1st material response or qq-s-763, cond a federal specification 2nd material response

NSN 5305-00-953-7032

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0