Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-953-7033

| · · · · · · · · · · · · · · · · · · · | |
|--|--|
| Thread Class: | |
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.312 inches | |
| Fastener Length: | |
| 1.737 inches | |
| Head Style: | |
| Flat chamfer | |
| Head Diameter: | |
| 0.218 inches | |
| Head Height: | |
| 0.480 inches | |
| First Diameter From Head: | |
| 0.120 inches | |
| Second Diameter From Head: | |
| 0.218 inches | |
| Third Diameter From Head: | |
| 0.120 inches | |
| Fourth Diameter From Head: | |
| 0.250 inches | |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: | |
| 0.070 inches | |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: | |
| 0.120 inches | |
| Distance From Largest Bearing Surface Of Head To End Of Third Diameter: | |
| 1.343 inches | |
| Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: | |
| 1.390 inches | |
| Internal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.190 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Externally Relieved Body Diameter Quantity: | |
| 4 | |
| Material: | |
| Steel comp 303 or steel comp 304 | |
| Material Specification: | |
| | |

Astm a582 assn standard 1st material response or qq-s-763 federal specification 2nd material response

Externally Relieved Body Screw - Page 2 of 2

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

