

View Online at <https://aerobasegroup.com/nsn/5305-00-954-2228>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.250 inches

Fastener Length:

0.625 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

First Diameter From Head:

Between 0.118 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.285 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Special Features:

Point style 6, 0.118 in . Min 0.125 in. Maximum dia. 0.090 in. Lg by 90 degrees of angle

Material:

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385

Material Specification:

66 federal standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0