NSN 5305-00-956-5778

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-956-5778 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 0.875 inches **Head Style:** Fillister **Head Diameter:** Between 0.303 inches and 0.321 inches **Head Height:** 0.086 inches **First Diameter From Head:** 0.087 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.625 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 302 or steel comp 303 or steel comp 430 **Material Specification:** Mil-s-7720 military specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization:

NSN 5305-00-956-5778

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.