

View Online at <https://aerobasegroup.com/nsn/5305-00-957-5710>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.688 inches and 0.706 inches

**Fastener Length:**

Between 1.321 inches and 1.370 inches

**Head Style:**

Oval countersunk

**Head Diameter:**

Between 0.755 inches and 0.760 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.802 inches and 0.822 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Steel comp 4130 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0