## NSN 5305-00-957-7033

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-957-7033 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.141 inches and 0.172 inches **Fastener Length:** Between 0.422 inches and 0.453 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.257 inches and 0.279 inches First Diameter From Head: Between 0.095 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.312 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1213 **Material Specification:** Astm a108 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-00-957-7033

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0