NSN 5305-00-957-7282

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-957-7282

| Thread Class. |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.089 inches and 0.125 inches |
| Fastener Length: |
| Between 0.094 inches and 0.125 inches |
| Head Style: |
| Flat countersunk undercut |
| Head Diameter: |
| Between 0.147 inches and 0.172 inches |
| Head Height: |
| Between 0.028 inches and 0.036 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.086 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Countersink Angle: |
| Between 80.0 degrees and 82.0 degrees |
| Screw Material: |
| Steel |
| Screw Material Specification: |
| 66 federal standard single material response or astma108 assn standard single material response |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Specification Or Standard: |
| 3 type and 2c style |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-00-957-7282

Machine Screw - Page 2 of 2



Fiig:

A500d0