## NSN 5305-00-957-7407



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-957-7407 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.305 inches and 0.335 inches **Fastener Length:** Between 0.958 inches and 0.988 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Shoulder Diameter:** 0.193 inches first shoulder and 0.195 inches first shoulder **Shoulder Length:** 0.653 inches first shoulder **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037 **Test Data Document:** 81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-957-7407

Shoulder Screw - Page 2 of 2



Fiig:

A003b0