NSN 5305-00-958-0602

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-958-0602

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.417 inches and 0.500 inches |
| Fastener Length: |
| 0.500 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.594 inches and 0.615 inches |
| Head Height: |
| Between 0.203 inches and 0.218 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.312 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Screw Material: |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 |
| Screw Material Specification: |
| 66 federal standard all material responses |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| |
| Shelf Life: |
| Shelf Life: N/a |
| |
| N/a |
| N/a |
| N/a Unit Of Measure: |
| N/a Unit Of Measure: Demilitarization: |