NSN 5305-00-958-8537

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-958-8537 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.470 inches **Fastener Length:** 1.250 inches **Head Style: Button Head Diameter:** 0.710 inches **Head Height:** 0.190 inches **Shoulder Diameter:** 0.497 inches first shoulder and 0.499 inches first shoulder **Shoulder Length:** 0.780 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.106 inches first hole **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 150 pounds per square inch **Criticality Code Justification:** Cqbc Distance From Head Largest Bearing Surface To Shank Hole Center: 1.125 inches first hole **Shoulder Shape:** Round first shoulder Material: Stainless steel **Surface Treatment: Passivate Thread Series Designator:**

Unf Shelf Life:

N/a

NSN 5305-00-958-8537

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0