## NSN 5305-00-959-1699

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-959-1699 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.756 inches and 0.806 inches **Fastener Length:** Between 2.141 inches and 2.171 inches **Head Style:** Flat countersunk **Head Diameter:** Between 1.014 inches and 1.017 inches **Grip Diameter:** Between 0.4985 inches and 0.4995 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4140 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-00-959-1699

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0