## NSN 5305-00-959-1910

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-959-1910 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.195 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.091 inches and 0.096 inches **Head Height:** Between 0.057 inches and 0.060 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.060 inches Width Across Flats: Between 0.050 inches and 0.051 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type Shelf Life:

N/a

## NSN 5305-00-959-1910

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0