4



| NSN 5305-00-959-2684 Machine Screw - Page 1 of 1 |
|--|
| View Online at https://aerobasegroup.com/nsn/5305-00-959-2684 |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| 2.750 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.452 inches and 0.507 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.250 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Countersink Angle: |
| Between 80.0 degrees and 82.0 degrees |
| Screw Material: |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 |
| Screw Material Specification: |
| 66 federal standard all material responses |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unc |
| Shelf Life: |

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0