## **NSN 5305-00-959-2702** Machine Screw - Page 1 of 1



| View Online  | at https://aerobasegroup.com/nsn/5305-00-959-2702              |
|--------------|--|
| Thread Cla   | SS:  |
| 2a           |  |
| Thread Dire  | ection:  |
| Right-hand   |  |
| Thread Len   | igth:  |
| 1.750 inche  | S  |
| Fastener Lo  | ength:   |
| 2.750 inche  | S  |
| Head Style:  | :  |
| -lat counter | sunk   |
| Head Diam    | eter:  |
| 3etween 0.8  | 568 inches and 0.635 inches                                    |
| Internal Dri | ve Style:  |
| Cross reces  | s type 1   |
| Thread Dia   | meter:   |
| 0.312 inche  | S  |
| Thready Qt   | y Per Inch (tpi):  |
| 24           |  |
| Min. Tensil  | e Strength (psi):  |
| 55000 poun   | ds per square inch   |
| Countersin   | k Angle:   |
| 3etween 80   | .0 degrees and 82.0 degrees                                    |
| Screw Mate   | erial:   |
| Steel comp   | 1010 or steel comp 1011 or steel comp 1013                     |
| Screw Mate   | erial Specification:   |
| 66 federal s | tandard all material responses                                 |
| Screw Surf   | ace Treatment:   |
| Cadmium a    | nd chromate  |
| Screw Surf   | ace Treatment Specification:                                   |
| Qq-p-416, ty | ype 2, class 3 federal specification single treatment response |
| Thread Ser   | ies Designator:  |
| Unf          |  |
| Shelf Life:  |  |
| N/a          |  |
| Unit Of Mea  | asure:   |
|              |  |
| Demilitariza | ation:   |
| No           |  |
| Fiig:        |  |
| A500d0       |  |