NSN 5305-00-959-2705

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-959-2705

| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 1.750 inches |
| Fastener Length: |
| 2.500 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.685 inches and 0.762 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| End Application: |
| Spec item |
| Thread Diameter: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Countersink Angle: |
| Between 80.0 degrees and 82.0 degrees |
| Screw Material: |
| Steel comp 1010 or steel comp 1011 or steel comp 1013 |
| Screw Material Specification: |
| 66 federal standard all material responses |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 type 2 cl 3 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |
| |