NSN 5305-00-959-5335

Close Tolerance Screw - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5305-00-959-5335

Thread Class:
3a Three d Direction
Thread Direction:
Right-hand
Thread Length:
Between 0.756 inches and 0.806 inches
Fastener Length: Between 2.204 inches and 2.234 inches
Head Style: Flat countersunk
Head Diameter:
Between 1.014 inches and 1.017 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.500 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Thready Qty Per Inch (tpi):
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp e4340 or steel comp 4340 or steel comp 8735 or steel comp 6150 or steel comp 4140
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 3 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-00-959-5335

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

