## NSN 5305-00-960-7450

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-960-7450 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.193 inches **Fastener Length:** 1.000 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: 0.375 inches **Hole Diameter:** 0.059 inches First Diameter From Head: 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.813 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 20 **Hole Configuration Style:** Hexagon flats **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate** 

**Surface Treatment Specification:** 

Mil-f-14072, finish e300 military specification single treatment response

## NSN 5305-00-960-7450

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-f-14072 spec.