## NSN 5305-00-961-8374

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-961-8374

**Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.125 inches and 1.250 inches **Fastener Length:** Between 1.312 inches and 1.375 inches **Head Style:** Hexagon extended washer **Head Height:** Between 0.439 inches and 0.604 inches Width Between Flats: Between 0.675 inches and 0.687 inches **Extended Washer Diameter:** Between 1.243 inches and 1.280 inches **Extended Washer Thickness:** Between 0.064 inches and 0.104 inches **Washer Quantity:** Single Shear Strength: 8190 pounds per square inch **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.437 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 55000 pounds per square inch **Primary Washer Outside Diameter:** Between 1.243 inches and 1.280 inches **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.064 inches and 0.104 inches Material:

Steel

**Material Specification:** 

Q-w-409 federal specification 13th material response

**Surface Treatment:** 

Cadmium

## NSN 5305-00-961-8374

Assembled Washer Screw - Page 2 of 2



Qq-p-416, type 2 federal specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0