# NSN 5305-00-964-0419

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-964-0419



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.827 inches and 0.920 inches

#### Fastener Length:

Between 0.969 inches and 1.000 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.332 inches and 0.385 inches

#### Internal Drive Style:

Cross recess type 1

#### **Thread Diameter:**

0.190 inches

#### Thready Qty Per Inch (tpi):

32

### Min. Tensile Strength (psi):

125000 pounds per square inch

#### Countersink Angle:

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Steel comp 8630 or steel comp 4037

#### Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

#### **Screw Surface Treatment:**

Cadmium and chromate

#### Screw Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

#### Thread Series Designator:

Unjf

# **Specification Data:**

80205-nas514 professional/industrial association standard

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A500d0

# NSN 5305-00-964-0419

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-6050 spec.

