

View Online at <https://aerobasegroup.com/nsn/5305-00-964-0675>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 2.250 inches and 2.562 inches

**Fastener Length:**

Between 2.562 inches and 2.750 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.591 inches and 0.627 inches

**Width Between Flats:**

Between 1.469 inches and 1.500 inches

**Thread Diameter:**

1.000 inches

**Thready Qty Per Inch (tpi):**

8

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

74.0 rockwell b

**Minimum Yield Strength:**

30000 pounds per square inch

**Surface Finish:**

63.0 microinches threads

**Material:**

Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 303f or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 384

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0