## NSN 5305-00-965-0074

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-965-0074 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.325 inches and 0.428 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.285 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Oxide film **Screw Surface Treatment Specification:** Mil-c-5541 military specification single treatment response **Special Features:** Painted area beige color no. 23531 federal standard 595 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0

## NSN 5305-00-965-0074

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.