Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-966-7092

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.938 inches	
Fastener Length:	
1.625 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
0.385 inches	
First Diameter From Head:	
0.150 inches	
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:	
0.604 inches	
Internal Drive Style:	
Slot	
Thread Diameter:	
0.190 inches	
Thready Qty Per Inch (tpi):	
32	
Minimum Yield Strength:	
40000 pounds per square inch	
Countersink Angle:	
Between 80.0 degrees and 82.0 degrees	
Externally Relieved Body Diameter Quantity:	
1	
Material:	
Steel comp 414	
Material Specification:	
Qq-s-763 federal specification single material response	
Surface Treatment:	
Passivate	
Test Data Document:	
98230-0n008469 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufac	turer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0