NSN 5305-00-966-7092

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-966-7092 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.938 inches **Fastener Length:** 1.625 inches **Head Style:** Flat countersunk **Head Diameter:** 0.385 inches **First Diameter From Head:** 0.150 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.604 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 40000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 414 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Test Data Document:** 98230-0n008469 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Thread Series Designator:** Unf Shelf Life:

N/a

Unit Of Measure:

NSN 5305-00-966-7092

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0