NSN 5305-00-968-0560

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-968-0560 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.280 inches and 0.340 inches **Fastener Length:** Between 0.970 inches and 1.030 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.375 inches and 0.385 inches **Head Height:** Between 0.098 inches and 0.116 inches **First Diameter From Head:** Between 0.145 inches and 0.155 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.532 inches and 0.634 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** 81.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Astm a108 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-00-968-0560

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0