

View Online at <https://aerobasegroup.com/nsn/5305-00-968-3487>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.200 inches and 0.250 inches

**Fastener Length:**

Between 0.219 inches and 0.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.166 inches and 0.183 inches

**Head Height:**

Between 0.069 inches and 0.079 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

**Screw Material Specification:**

66 federal standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

81348-ff-s-92 government specification and 88818-h71916 manufacturers standard

**Specification Or Standard:**

3 type and 4c style and 4-40 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0