NSN 5305-00-968-3487

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-968-3487 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Fillister **Head Diameter:** Between 0.166 inches and 0.183 inches **Head Height:** Between 0.069 inches and 0.079 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Screw Material Specification:** 66 federal standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Data:** 81348-ff-s-92 government specification and 88818-h71916 manufacturers standard **Specification Or Standard:** 3 type and 4c style and 4-40 size Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-968-3487 Machine Screw - Page 2 of 2



Fiig:

A500d0