## NSN 5305-00-968-3514

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-968-3514 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.000 inches and 1.250 inches **Fastener Length:** 2.000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.480 inches and 0.531 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5305-00-968-3514

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0