Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-968-7765

| Thread Class:   |  |
|---|--|
| 2a  |  |
| Thread Direction:   |  |
| Right-hand  |  |
| Thread Length:  |  |
| 1.438 inches  |  |
| Fastener Length:  |  |
| 1.938 inches  |  |
| Head Style:   |  |
| Pan no. 2   |  |
| Head Diameter:  |  |
| 0.270 inches  |  |
| Head Height:  |  |
| 0.082 inches  |  |
| First Diameter From Head:   |  |
| 0.095 inches  |  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |  |
| 0.500 inches  |  |
| Internal Drive Style:   |  |
| Cross recess type 1   |  |
| Thread Diameter:  |  |
| 0.138 inches  |  |
| Thready Qty Per Inch (tpi):   |  |
| 32  |  |
| Minimum Yield Strength:   |  |
| 45000 pounds per square inch  |  |
| Externally Relieved Body Diameter Quantity:                             |  |
| 1   |  |
| Material:   |  |
| Steel comp 303  |  |
| Material Specification:   |  |
| Qq-s-763 federal specification single material response                 |  |
| Surface Treatment:  |  |
| Passivate   |  |
| Thread Series Designator:   |  |
|   |  |
| Shelf Life:   |  |
| N/a   |  |
| Unit Of Measure:  |  |
|   |  |
| Demilitarization:   |  |
| No  |  |
|   |  |

## NSN 5305-00-968-7765

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

