## NSN 5305-00-969-4345

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-969-4345



### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

#### Thread Length:

Between 0.117 inches and 0.188 inches

#### Fastener Length:

Between 0.156 inches and 0.188 inches

#### Head Style:

Pan

Head Diameter:

Between 0.473 inches and 0.492 inches

#### **Head Height:**

Between 0.162 inches and 0.175 inches

#### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.250 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

#### **Product Name:**

Navy special project

#### **Screw Material:**

Steel comp 4140 or steel comp e4340 or steel comp 8740

#### **Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

#### Screw Surface Treatment:

Cadmium

#### **Screw Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

#### Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas604 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5305-00-969-4345

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.

