Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-973-0929

Thread Class: 2a Thread Direction: Right-hand Thread Length: 1.750 Incles Fastener Length: 1.750 Incles Fastener Length: 1.750 Incles Head Style: Fillster Head Style: Fillster Head Diamoter: 0.226 Incles Head Height: 0.128 Incles First Diameter From Head: 0.128 Incles Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.128 Incles Internal Drive Style: Cross recess type 1 Thread Diameter: 0.134 Incles Thread Diameter: 0.144 Incles Thread Diameter: 0.145 Incles Corpore rationy Surface Treatment: Corpore rationy Guardiant Corpore alony Surface Treatment: Corpore alony Corpore alony Direct Treatment: Corpore alony Direct Treatmen	-	
Tread Direction:Right-handTread Length:1.750 inchesRatener Length:2.125 inchesHead Style:PillstarHead Style:Co226 inchesHead Height:0.228 inchesBillstarPillstar1.750 inchesDistance From Head:0.132 inchesPillstar0.132 inchesFirst Diameter From Head:0.132 inchesPillstar0.132 inchesPillstar1.750 inches From Largest Bearing Surface Of Head To End Of First Diameter:0.751 inches1.751 inches1.755 inchesPillstar1.755 inches2.755 inches2.755 inches2.755 inches2.755 inches1.755 inches2.755 inches2.755 inches2.755 inches2.755 inches2.755 inches2.755 inches2.755 inches2.755 inches2.755 inches3.75 inches </th <th>Thread Class:</th> <th></th>	Thread Class:	
Right-hand Tread Length: 1.750 Inches Fastener Length: 2.125 Inches Head Style: Fillister Head Style: 1.750 Inches Head Height: 0.132 Inches Distance From Head: 0.132 Inches Distance From Head: 0.375 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 Inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 Inches Thread Olameter: 0.376 Inches Thread Vilve Per Inch (tpl): 32 Cadmium Cadmium Cadmium Cadmium Thread Series Designator: Ince Shef Lite: Na Cadmium Thread Series Designator: Ince Shef Lite: Na Dit Of Measure: Ince	2a	
Tread Langth: 1.750 inches Fastener Langth: 2.125 inches Head Style: Fillistor Head Diameter: 0.226 inches Head Height: 0.132 inches First Diameter From Head: 0.132 inches Distance From Langest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Diameter Candinui Thread Series Designator: Unc Sheff Life: Na Dindottasure: Dindottas	Thread Direction:	
1.750 inclusi Fastener Length: 2.125 inclusi Head Siyle: Fillister 10226 inclusi Head Member: 0.226 inclusi Head Nameter: 0.226 inclusi Head Height: 0.123 inclusion D.128 inclusion	Right-hand	
Fastener Length: 2.125 inches Head Style: Fillsr Head Diameter: 0.226 inches Head Height: 0.132 inches Filts Diameter From Head: 0.132 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross racess type 1 Thread Diameter: 0.144 inches Thread Diameter: 0.144 inches Thread Diameter: 0.152 Cross racess type 1 Thread Diameter: 0.144 inches Thread Diameter: 0.145 inches Thread Diameter: 0.152 Caternality Relieved Body Diameter Quantity: 1 Material: Copper alloy Summer: Ince Summer: Ince Summer: Ince Ince Threatment: Ince Threatment: Ince Ince Theatine: Ince Theatine	Thread Length:	
2.125 incles Head Style: Fillister Head Diameter: 0.226 incles Head Height: 0.132 incles First Diameter From Head: 0.128 incles Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 incles Internal Drive Style: 0.164 incles Thread Diameter: 0.164 incles Thready Oty Per Inch (tpl): 32 Externally Relieved Body Diameter Quantity: 1 Copper alloy Surface Treatment: Coded To End Science Tool Intread Series Designator: Interd S	1.750 inches	
Head Style: Filister Head Diameter: 0.228 inches Head Height: 0.132 inches D.132 inches D.128 inches D.128 inches D.128 inches Distance From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thread Qity Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Capper alloy Surface Treatment: Cadmim Thread Series Designator: Inc Stoff Life: Na Diel Measure: Inc Stoff Measure: Inc Beniltarization: Na Inc Informal Drive Style: Inc Beniltarization: Inc Informal Drive Style: Informal Driv	Fastener Length:	
Filiater Head Diameter: 0.226 inches Head Height: 0.128 inches First Diameter From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Gty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Inc Via Fired Infores Fired Series Designator: Inc Sinfore Treatment: Inc Interd Series Designator: Inc Na Interd Series Designator: Inc Interd Series Designator: Inc Interd Series Designator: Inc Interd Series Designator: Inc Series Designator: Interd Series Designator:	2.125 inches	
Head Diameter: 0.226 inches Head Height: 0.132 inches First Diameter From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Inor Via Inord Measure: Inord Measure: Inord Measure: Inord Measure: Inord Measure: Image:	Head Style:	
0.228 inches Head Height: 0.132 inches First Diameter From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Interail Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Atternall Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Indexini Copper alloy Surface Treatment: Incel Thread Series Designator: Incel Incel Surface Treatment: Incel Incel Incel Incel Interface Interface <	Fillister	
Head Height: 0.132 inches First Diameter From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Interail Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Atternall Relieved Body Diameter Quantity: 1 Copper alloy Surface Treatment: Cadmium Thread Series Designator: Inc Material: Copper alloy Buff Chile: Na Dinc Fined Series Designator: Inc Surface Treatment: Na Interdifference Na Surface Treatment: Interdifference Interdifference Interdifference Interdifference Interdifference Interdifference Interdifference Interdifference Interdifference Interediffe	Head Diameter:	
0.132 inchesFirst Diameter From Head:0.128 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:0.375 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloySurface Treatment:CadmiumThread Series Designator:UncSuff Life:NaFinel Internation:NaFinel Internation:Finel Internation: </th <th>0.226 inches</th> <th></th>	0.226 inches	
First Diameter From Head: 0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: Na Panelitarization: No Fig:	Head Height:	
0.128 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Ince Vinc Sheff Life: Na Init of Measure: Init of Measure Init of Measure <th>0.132 inches</th> <th></th>	0.132 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter:0.375 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloySurface Treatment:CadmiumThread Series Designator:ViaMaterial:NoPinel Information:NaFig:NoFig:NoFig:	First Diameter From Head:	
0.375 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demiltarization: No Fig:	0.128 inches	
Internal Drive Style:Cross recess type 1Thread Diameter:0.164 inchesThready Qty Per Inch (tpi):32Externally Relieved Body Diameter Quantity:1Material:Copper alloySurface Treatment:CadmiumThread Series Designator:VincShelf Life:N/aDin of Measure:Pomilitarization:NoFig:	Distance From Largest Bearing Surface Of Head To End Of First	Diameter:
Cross recess type 1 Thread Diameter: O.164 inches Thready Qty Per Inch (tpi): Gate Composition of the Compos	0.375 inches	
Thread Diameter: 0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Dinc Of Measure: - Pernilitarization: No Fig:	Internal Drive Style:	
0.164 inches Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Vin Dint Of Measure: Demiltarization: No Fig:	Cross recess type 1	
Thready Qty Per Inch (tpi): 32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	Thread Diameter:	
32 Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Dhit Of Measure: Demilitarization: No Fiig:	0.164 inches	
Externally Relieved Body Diameter Quantity: 1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thready Qty Per Inch (tpi):	
1 Material: Copper alloy Surface Treatment: Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32	
Material:Copper alloySurface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:Pemilitarization:NoFig:	Externally Relieved Body Diameter Quantity:	
Copper alloy Surface Treatment: Cadmium Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Foemilitarization: No Fig:	1	
Surface Treatment:CadmiumThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:	
Cadmium Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Copper alloy	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fig:	Unc	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
	No	
A003b0	Fiig:	
	A003b0	