

View Online at <https://aerobasegroup.com/nsn/5305-00-977-8899>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.313 inches

Fastener Length:

0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.207 inches and 0.225 inches

Locking Feature:

Patch threads or strip threads

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.112 inches

Thready Qty Per Inch (tpi):

40

Countersink Angle:

Between 99.0 degrees and 100.0 degrees

Material:

Steel comp 202 or steel comp 302 or steel comp 304 or steel comp 303se or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp t15 or steel comp 403 or steel comp 405 or steel comp 410 or steel comp 414 or steel comp 416 or steel comp 416se or steel comp 420 or steel comp 429 or steel comp 430 or steel comp 430f or steel comp 430fse or steel comp 431 or steel comp 440a or steel comp 440b or steel comp 440c or steel comp 440f or steel comp 446

Surface Treatment:

Passivate

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0