## NSN 5305-00-978-9345

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-978-9345 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.734 inches and 0.766 inches **Fastener Length:** Between 0.734 inches and 0.766 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches Width Between Flats: Between 0.093 inches and 0.095 inches **Internal Drive Style:** Err-090 **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.093 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 45.0 rockwell c **Screw Material:** Steel **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2 cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5305-00-978-9345** Machine Screw - Page 2 of 2



Fiig:

A500d0