## NSN 5305-00-978-9348

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-978-9348 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Width Between Flats: Between 0.1094 inches and 0.1111 inches **Internal Drive Style:** Err-090 **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel uns k03104 **Screw Material Specification:** Astm a574 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification all treatment responses or mil-c-81562 type 2 cl 6 military specification all treatment responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-978-9348

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-81562 spec.