## NSN 5305-00-978-9378

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-978-9378 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.369 inches and 0.500 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-978-9378

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0