

View Online at <https://aerobasegroup.com/nsn/5305-00-979-7815>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.190 inches and 0.215 inches

Fastener Length:

Between 0.463 inches and 0.493 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.220 inches and 0.230 inches

Head Height:

Between 0.082 inches and 0.107 inches

Shank Unthreaded Hole Diameter:

0.035 inches first hole and 0.040 inches first hole

First Diameter From Head:

Between 0.160 inches and 0.170 inches

Second Diameter From Head:

Between 0.320 inches and 0.330 inches

Third Diameter From Head:

Between 0.108 inches and 0.112 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.065 inches and 0.075 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.103 inches and 0.118 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.263 inches and 0.288 inches

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.033 inches first hole and 0.038 inches first hole

Externally Relieved Body Diameter Quantity:

3

Material:

Steel comp 410 or steel comp 303

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0