

View Online at <https://aerobasegroup.com/nsn/5305-00-979-7815>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.190 inches and 0.215 inches

**Fastener Length:**

Between 0.463 inches and 0.493 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.220 inches and 0.230 inches

**Head Height:**

Between 0.082 inches and 0.107 inches

**Shank Unthreaded Hole Diameter:**

0.035 inches first hole and 0.040 inches first hole

**First Diameter From Head:**

Between 0.160 inches and 0.170 inches

**Second Diameter From Head:**

Between 0.320 inches and 0.330 inches

**Third Diameter From Head:**

Between 0.108 inches and 0.112 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.065 inches and 0.075 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.103 inches and 0.118 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 0.263 inches and 0.288 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.033 inches first hole and 0.038 inches first hole

**Externally Relieved Body Diameter Quantity:**

3

**Material:**

Steel comp 410 or steel comp 303

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0