## NSN 5305-00-980-8884

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-980-8884 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.216 inches **Fastener Length:** Between 0.403 inches and 0.423 inches **Head Style:** Hexagon **Head Height:** Between 0.035 inches and 0.045 inches Width Between Flats: Between 0.151 inches and 0.161 inches **Shoulder Diameter:** 0.110 inches first shoulder and 0.113 inches first shoulder **Shoulder Length:** 0.197 inches first shoulder and 0.203 inches first shoulder **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5305-00-980-8884

Shoulder Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.