NSN 5305-00-983-6633

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-983-6633 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.826 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** Between 0.430 inches and 0.438 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.438 inches Width Across Flats: Between 0.375 inches and 0.379 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-983-6633

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0