NSN 5305-00-983-6665

Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-00-983-6665

| Thread Class: | |
|--|------------------|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.960 inches and 1.000 inches | |
| Fastener Length: | |
| Between 1.710 inches and 1.750 inches | |
| Head Style: | |
| Flat chamfer | |
| Head Diameter: | |
| Between 0.365 inches and 0.375 inches | |
| Head Height: | |
| Between 0.244 inches and 0.250 inches | |
| Internal Drive Style: | |
| Hexagon | |
| Thread Diameter: | |
| 0.250 inches | |
| Width Across Flats: | |
| Between 0.187 inches and 0.190 inches | |
| Thready Qty Per Inch (tpi): | |
| 28 | |
| Min. Tensile Strength (psi): | |
| 160000 pounds per square inch | |
| Hardness Rating: | |
| 36.0 rockwell c and 45.0 rockwell c | |
| Minimum Yield Strength: | |
| 130000 pounds per square inch | |
| Material: | |
| Steel | |
| Surface Treatment: | |
| Cadmium and chromate | |
| Surface Treatment Specification: | |
| Ams-qq-p-416, type 2, cl 2 federal specification single tr | eatment response |
| Thread Series Designator: | |
| Unf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5305-00-983-6665

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

