## NSN 5305-00-983-6671

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-983-6671 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.886 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.468 inches **Head Height:** Between 0.306 inches and 0.312 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type Shelf Life:

N/a

## NSN 5305-00-983-6671

Socket Head Cap Screw - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0