## NSN 5305-00-983-8079

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-983-8079 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.579 inches and 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.938 inches **Head Height:** Between 0.616 inches and 0.625 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 6 type Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-983-8079

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0