## NSN 5305-00-983-8101

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-983-8101 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.264 inches and 0.295 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.133 inches and 0.156 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Primary Washer Outside Diameter:** Between 0.243 inches and 0.257 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.031 inches and 0.041 inches Material: Steel **Material Specification:** Sae gr 3 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** 9.3026 fscm 70926 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-00-983-8101

Assembled Washer Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0