

View Online at <https://aerobasegroup.com/nsn/5305-00-983-9826>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.333 inches and 0.343 inches

**Fastener Length:**

Between 0.448 inches and 0.478 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.306 inches and 0.322 inches

**Head Height:**

Between 0.105 inches and 0.115 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Screw Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5626 spec.