NSN 5305-00-983-9827



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-983-9827 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.333 inches and 0.343 inches **Fastener Length:** Between 0.573 inches and 0.603 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Fiig: A500d0

No

Unit Of Measure:

Demilitarization:

NSN 5305-00-983-9827

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.