## NSN 5305-00-984-1049

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-984-1049 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.310 inches **Fastener Length:** 0.687 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches **First Diameter From Head:** Between 0.117 inches and 0.123 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.377 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 302 or steel comp 303 or steel comp 304 **Material Specification:** Qq-s-763 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-00-984-1049

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0