NSN 5305-00-984-3022

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-984-3022 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.065 inches and 1.403 inches **Fastener Length:** Between 3.190 inches and 3.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.313 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-00-984-3022

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0