NSN 5305-00-984-6193

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-984-6193



Thread Class: 2a **Thread Direction: Right-hand Thread Length:** Between 0.438 inches and 0.500 inches Fastener Length: 0.500 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Cross recess type 1 **End Application:** Nsn 4210-01-486-1035 tfft (tactical fire fighting truck) **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1010 or steel comp 1011 or steel comp 1013 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 9c style Shelf Life: N/a Unit Of Measure: ---

Demilitarization:

No

NSN 5305-00-984-6193 Machine Screw - Page 2 of 2

Fiig: A500d0

