

View Online at <https://aerobasegroup.com/nsn/5305-00-984-6805>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.276 inches and 0.312 inches

**Fastener Length:**

Between 0.281 inches and 0.312 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.136 inches and 0.140 inches

**Head Height:**

Between 0.044 inches and 0.053 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

Between 248.0 brinell standard and 321.0 brinell standard

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5735 assn standard single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Data:**

80205-nas1101 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5002 spec.